

TECNOMAX

TECNOMAX ROUTER

Mechanical router equipped with tilting head with neck depth 600, 800 and 900mm. The large cast iron worktable guarantees stable support even for large work pieces. A hand wheel in front of the operator allows easy vertical worktable adjustment. The routing head is equipped with 6 adjustable turret stops to facilitate the return to machining positions.



Technical specifications:

		ROUTER 600 (24")	ROUTER 800 (32")	ROUTER 900 (36")
Spindle head and frame distance	mm	600	800	900
Spindle speeds	rpm	9000-18000	9000-18000	900-18000
Motor power				
60 Hz (600V / 3ph)	hp	1,4/3,6	3,6/4,8	3,6/4,8
60 Hz (220V / 1ph)	hp	2,5	2,5	2,5
Vertical spindle stroke	mm	80 (3 ¹ / ₄ ")	80 (3 ¹ / ₄ ")	80 (3 ¹ / ₄ ")
Revolving turret with adjust. stops	n.	6	6	6
Vertical table stroke	mm	150 (6")	150 (6")	150 (6")
Max. table-spindle distance	mm	195 (7 ³ / ₄ ")	195 (7 ³ / ₄ ")	195 (7 ³ / ₄ ")
Table dimensions(non CE)	mm	800x600	800x600	960X960
	Inch	31 ¹ / ₂ " x 23 ¹ / ₂ "	31 ¹ / ₂ " x 23 ¹ / ₂ "	37 ³ / ₄ " x 37 ³ / ₄ "
Max. height of table from floor	mm	1050 (41 ¹ / ₄ ")	1050 (41 ¹ / ₄ ")	1050 (41 ¹ / ₄ ")
Net weight basic machine	Kg	235 (517 lbs)	285 (627 lbs)	320 (704 lbs)
Copying pin diam.	mm	10-12	10-12	10-12
Spindle coupling Morse taper	n.	2	2	2
Cutter-bit diam.	mm	10	10	10
Collets diam.	mm	6-8-9,5	6-8-9,5	6-8-9,5